

UV-B Narrowband TL

TL 40W/01 RS

More than 400 independent clinical studies have proven that the UVB Narrowband TL lamps are safer and more effective than any other lamps in their class. That is because these lamps emit only a very narrow waveband from the 'B' bandwidth of the UV spectrum (290 to 315). This narrow waveband is between 305 and 315 nm and peaks at 311 nm: the most efficacious waveband for the treatment of psoriasis. This means that treatment is much more focused and exposure times are much shorter. This in turn leads to a reduction of side effects such as reddening of the skin and itching. All of this makes them ideal for phototherapy treatment of diseases such as psoriasis, parapsoriasis, vitiligo, atopic dermatitis, and mycosis fungoides. What's more, because the overall dosage of this narrowband radiation can be closely controlled, these lamps are suitable for home therapy.

Product data

• General Characteristics

System Description Rapid Start Cap-Base G13 Bulb T38

Main Application Medical Therapy

• Light Technical Characteristics

Color Code 01
Color Designation (text)
Chromaticity Coordinate X
Chromaticity Coordinate Y
Depreciation 500 10 %
hours

O1
Ultra Violet B
Ultra Violet B
192 192 193 194 195 196 197

• Electrical Characteristics

Lamp Wattage 40 W Lamp Wattage Technical Lamp Voltage 104 V Lamp Current 0.43 A

UV-related Characteristics

UV-B Radiation 7.5 W 100hr (IEC) UV-B Radiation 5hr (IEC)

• Product Dimensions

Base Face to Base 7199.4 (max) mm 7191.4 (min), 1206.5 (max) mm 7191.4 (min), 1206.5 (max) mm 7191.4 (min), 1206.5 (max) mm 7191.4 (max) mm 7191.4 (min), 1206.5 (max) mm 7191.4 (max) mm 7191

928011300101

7.7 W

• Product Data Order code


Full product code 928011300101 TL 40W/01 RS Full product name TL 40W/01 RS Order product name Pieces per pack Packing configuration 25 Packs per outerbox 8711500264749 Bar code on pack -EAN1 8711500264756 Bar code on outerbox - EAN3 928011300101 Logistic code(s) -12NC 292.000 gr Net weight per piece




Dimensional drawing


TL 40W/01 RS

| Product | A (Max) | B (Min) | B (Max) | C (Max) | D (Max) | |
|--------------|---------|---------|---------|---------|---------|--|
| TL 40W/01 RS | 1199.4 | 1204.1 | 1206.5 | 1213.6 | 40.5 | |



Photometric data







 $\ \odot$ 2013 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.