

TUV PL-L

TUV PL-L 35W/4P HO 1CT

TUV PL-L lamps are compact UVC (germicidal) lamps used in professional water and air disinfection units. The compact size of the lamp allows for a small system design and design flexibility. TUV PL-L lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Thanks to the single-ended lamp base, lamp replacement is easy.

Product data

• General Characteristics

System Description 2G11 Cap-Base Cap-Base Information 4 Pins Bulb 2xT16 Execution

Main Application Disinfection Useful Life 9000 hr

• Light Technical Characteristics

TUV Color Code Color Designation (text)

• Electrical Characteristics

35 W Lamp Wattage Lamp Wattage Tech-35 W nical Lamp Voltage 42 V Lamp Current 0.85 A

• UV-related Characteristics

UV-C Radiation 11.0 W

Dimensional drawing

• Product Dimensions

Base Face to Base 195 (max) mm Face A 220 (max) mm Insertion Length B 225 (max) mm Overall Length C 39 (max) mm Diameter D Diameter D1 18 (max) mm

• Product Data

Bar code on pack -

927904204007 Order code Full product code 927904204007 Full product name TUV PL-L 35W/4P HO 1CT TUV PL-L 35W/4P HO 1CT/25 Order product name Pieces per pack 25 Packing configuration Packs per outerbox

8711500888273


EAN1 8711500888280 Bar code on

outerbox - EAN3 Logistic code(s) -927904204007

Net weight per piece 60.900 gr




Dimensional drawing





TUV PL-L 35W/4P HO 1CT

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
TUV PL-L 35W/4P HO	195	220	225	39	18



Photometric data







 $\ \odot$ 2013 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.