



## Xitanium LED drivers - lite programmable

## Xi LP 75W 0.5-1.5A S1 230V C133 sXt

Philips Xitanium lite programmable Xtreme LED drivers are value engineered to deliver a carefully selected feature set and high-end performance, making it a preferred choice for many outdoor applications. The portfolio offers high flexibility with a customizable operating window, enabling differentiation in LED lighting designs via system tuning and being prepared for LED efficacy upgrades. Configuration of programmable drivers has never been easier with the integrated SimpleSet feature, a fast and wireless way to change and read-out settings.

## **Product data**

General Information	
Nominal lifetime	100,000 hour(s)
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Maximum Efficiency at Full Load	89 %
Output Current (Max)	1500 mA
Open Circuit Voltage (DC) (Max)	120 V
Inrush Current Peak (Max)	43 A
Output Power (Max)	75 W
Inrush Current Width to 50% of Peak	270 μs
Diagnostics	True
Output Power (Min)	3.8 W
Output Current (Min)	500 mA
Output Voltage (Max)	75 V
Output Voltage (Min)	25 V

System characteristics	
Central DC Operation	No
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	70 ℃
T-Case Maximum (Max)	80 ℃
Controls and Dimming	
Dimmable	1-10V
Dimming Range	100-10 %
D4i compliant	No
DynaDimmer	Yes
Constant light output	Yes
Mechanical and Housing	
Product Length	133 mm
Housing	C133_LP_S1

Datasheet, 2024, March 19 data subject to change

## Xitanium LED drivers - lite programmable

Overall length	133 mm
Overall width	77 mm
Overall height	39.5 mm
Dimensions (Height x Width x Depth)	40 x 77 x 133 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV
	differential mode and 10 kV common mode
Isolation Classification	Class I and Class II
Approval Marks	CCC certificate CE marking CB Certificate ENEC
	certificate
Output Current Set Options	SimpleSet
Protection class IEC	Safety class I/II

Product Data	
Order product name	Xi LP 75W 0.5-1.5A S1 230V C133 sXt
Full product name	Xi LP 75W 0.5-1.5A S1 230V C133 sXt
Full product code	871869961032600
Order code	929001654906
Material Nr. (12NC)	929001654906
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699610326
Numerator - Packs per outer box	12
EAN/UPC - Case	8718699610333

