

## Lok-it! 1200 W 80 V/32/P50

Lok-it! | Halogen lamps



### Product family benefits

- Optimum use of the generated light in the spotlight



# Product datasheet

## Technical data

### Product information

Order reference	LOK-IT! 1200W/3
-----------------	-----------------


### Electrical data

Nominal voltage	80.0 V
Nominal wattage	1200.00 W
On-mode power	1265.00 W
Energy consumption in on-mode	1265.0 kWh/1000h

### Photometrical data

Color temperature	3200 K
Color rendering index Ra	100
Φuse value refers to luminous flux ..	360
Correlated color temperature CCT	3308 K
Useful luminous flux (Φuse)	27865 lm
Chromaticity coordinate x	0.416
Chromaticity coordinate y	0.395

### Dimensions & weight



Diameter	23.0 mm
Length	140.0 mm
Light center length (LCL)	84.0 mm
Illuminated field	14.7*14.5 mm <sup>2</sup>

### Lifespan

Lifespan	250 h
----------	-------

## Product datasheet

### Additional product data

Lighting technology used	HL
--------------------------	----

### Capabilities

Burning position	Any
------------------	-----

### Certificates & standards

Energy efficiency class	G
-------------------------	---

### Country specific categorizations

ANSI code	Other
Order reference	LOK-IT! 1200W/3

### Logistical data

EAN 10 of contained light source	4008321382795
----------------------------------	---------------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	15-03-2024
Primary Article Identifier	4008321382795
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

## Product datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321382795	Lok-it! 1200 W 80 V/32/P50	Folding carton box 1	70 mm x 70 mm x 160 mm	0.78 dm <sup>3</sup>	178.00 g
4008321382801	Lok-it! 1200 W 80 V/32/P50	Shipping carton box 12	294 mm x 222 mm x 175 mm	11.45 dm <sup>3</sup>	2341.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---