



UVB Broadband TL

TL 100W/12 SLV/10

The UVB Broadband TL lamps emit radiation in the 'B' bandwidth of the UV spectrum (290 to 315 nm) . This make these lamps suitable for various applications such as photo-therapy, agriculture & curing

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Photobiological Safety – IEC 62471 - Risk Group 3. WARNING - UV is emitted from these products.

Product data


General Information		Voltage (Nom)	
Cap-Base	R17D [R17d (RDC)]	126 V	
Life to 50% Failures (Nom)	1,000 hour(s)	Mechanical and Housing	
Useful Life (Nom)	1,000 hour(s)	Bulb Shape	T38
Light Technical		Approval and Application	
Color Code	12	Mercury (Hg) Content (Nom)	14.0 mg
Color Designation	Ultra Violet B	UV	
Chromaticity Coordinate X (Nom)	240	UV-B Radiation 100 hr (IEC)	13.5 W
Chromaticity Coordinate Y (Nom)	250	UV-B Radiation 5hr (IEC)	14.3 W
UV Depreciation at 1000 h	15 %	Product Data	
UV Depreciation at 500 h	10 %	Order product name	TL 100W/12 SLV/10
Operating and Electrical		Full product name	TL 100W/12 SLV/10
Power Consumption	100 W	Full product code	871869666241000
Lamp Current (Nom)	0.97 A	Order code	928034901230
Voltage (Nom)	126 V	Material Nr. (12NC)	928034901230

UVB Broadband TL

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696662410
Numerator - Packs per outer box	10


EAN/UPC - Case	8718696662427
----------------	---------------

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 100W/12 SLV/10	40.5 mm	1,763.8 mm	1,770.9 mm	1,768.5 mm	1,782.2 mm

Photometric data



Spectral Power Distribution Colour - TL 100W/12 SLV/10

