

64583 1000 W 240 V

Halogen studio lamps, double-ended



Areas of application

- Professional film and TV work
- Theater and concert stages
- Entertainment

Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 3,200 K (for professional film and TV work)
- Color temperature: 3,400 K (for maximum luminous efficacy)



Technical data

Product information

| Order reference 64583 1000W 240 |
|--|
|--|


Electrical data

| Nominal wattage | 1000.00 W |
|--|-----------|
| Nominal voltage | 240 V |
| On-mode power | 1020.00 W |
| Energy consumption in on-mode 1020.0 kWh/1000h | |

Photometrical data

| Color temperature | 3200 К |
|------------------------------------|----------|
| Color rendering index Ra | 100 |
| Luminous efficacy | 28 lm/W |
| Ouse value refers to luminous flux | 360 |
| Correlated color temperature CCT | 3250 К |
| Useful luminous flux (Физе) | 27645 lm |
| Chromaticity coordinate x | 0.420 |
| Chromaticity coordinate y | 0.397 |

Dimensions & weight



| Diameter | 12.0 mm |
|---|-----------|
| Length | 114.2 mm |
| Length with base excl. base pins/connection | 114.20 mm |

Lifespan

| Lifespan | 300 h |
|----------|-------|
| | |

Additional product data

| Base (standard designation) | R7s |
|-----------------------------|-----|
| Lighting technology used | HL |

Capabilities

| Burning position | Any |
|------------------|-----|
| | |

Certificates & standards

| Energy efficiency class | G |
|-------------------------|---|

Country specific categorizations

| ANSI code | Other | | |
|-----------------|-----------------|--|--|
| LIF | P2/20 | | |
| Order reference | 64583 1000W 240 | | |

Logistical data

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | |
|---|------------------------------------|--|--|--|
| Date of Declaration 15-03-2024 | | | | |
| Primary Article Identifier | 4050300411477 | | | |
| Candidate List Substance 1 | No declarable substances contained | | | |
| Declaration No. in SCIP database No declarable substances contained | | | | |

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------|---------------------------------|---|----------------------|--------------|
| 4050300411477 | 64583 1000 W 240 V | Folding carton box 1 | 26 mm x 26 mm x 163 mm | 0.11 dm³ | 22.00 g |
| 4050300411484 | 64583 1000 W 240 V | Shipping carton box 12 | 175 mm x 117 mm x 95 mm | 1.95 dm ³ | 324.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

A summary of studio lamps can be found on the halogen studio lamps poster. For more information on halogen lamps for studio, stage and TV see the brochure: "Good news for show business" "Halogen High Voltage Lamps" cross reference list

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.