PHILIPS Lighting



MSD Platinum (Touring/Stage)

MSD Platinum 200 Flex 1CT/8

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical		
Cap-Base	- [-]	Power Consumption	240 W	
Operating Position	UNIVERSAL [Any or Universal (U)]			
Life to 50% Failures (Nom)	2,000 h	Controls and Dimming		
		Dimmable	Yes	
Light Technical				
Color Code	2	Product Data		
Luminous Flux	14,000 lm	Order product name MSD Platinum 200 Flet		
Chromaticity Coordinate X (Nom)	0.300	Full product name	MSD Platinum 200 Flex 1CT/8	
Chromaticity Coordinate Y (Nom)	0.305	Full product code 871869680813900		
Correlated Color Temperature (Nom)	7800 K	Order code 928495705314		
Arc Length O (Nom)	0.8 mm	Material Nr. (12NC)	928495705314	
		Numerator - Quantity Per Pack	1	

MSD Platinum (Touring/Stage)


EAN/UPC - Product/Case	8718696808139		
Numerator - Packs per outer box	8		
EAN/UPC - Case	8718696808146		

Dimensional drawing





Photometric data



Spectral Power Distribution Colour - MSD Platinum 200 Flex 1CT/8



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

Product	D (max)	0	C (max)	т
MSD Platinum 200 Flex 1CT/8	56.5 mm	0.8 mm	60 mm	7 mm